



WPPS12W



WPPS12



## Metalclad Wall Switches (10A)

### Characteristics:

- Unique patented LOOP terminal to allow neutral looping at the switch.
- Complies with BS EN 60669-1, a.c only.
- 'X' rated - No need to de-rate for fluorescent loads.
- Capacity of each terminal 2 x 4.0mm<sup>2</sup> conductors.

Description	Cat ref. Plate Only	Cat ref. With Backbox Without Knockouts	Cat ref. With Backbox With Knockouts
-------------	---------------------	---	--------------------------------------

### Wall Switches White

10AX 1 Gang 2 Way Wall Switch	<b>WPPS12W</b>	<b>WPPS12BW</b>	<b>WPPS12BKOW</b>
10AX 2 Gang 2 Way Wall Switch	<b>WPPS22W</b>	<b>WPPS22BW</b>	<b>WPPS22BKOW</b>
10AX 3 Gang 2 Way Wall Switch	<b>WPPS32W</b>	<b>WPPS32BW</b>	<b>WPPS32BKOW</b>
10AX Push Switch	<b>WPPS12RW</b>	<b>WPPS12RBW</b>	<b>WPPS12RBKOW</b>

### Wall Switches Grey

10AX 1 Gang 2 Way Wall Switch	<b>WPPS12</b>	<b>WPPS12B</b>	<b>WPPS12BKO</b>
10AX 2 Gang 2 Way Wall Switch	<b>WPPS22</b>	<b>WPPS22B</b>	<b>WPPS22BKO</b>
10AX 3 Gang 2 Way Wall Switch	<b>WPPS32</b>	<b>WPPS32B</b>	<b>WPPS32BKO</b>
10AX Push Switch	<b>WPPS12R</b>	<b>WPPS12RB</b>	<b>WPPS12RBKO</b>

## Metalclad Wall Switches (20A)

### Characteristics:

- Unique patented LOOP terminal to allow neutral looping at the switch.
- Complies with BS EN 60669-1, a.c only.
- Capacity of each terminal 2 x 6.0mm<sup>2</sup> conductors.



WPDP84FO

Description	Cat ref. Plate Only	Cat ref. With Backbox Without Knockouts	Cat ref. With Backbox With Knockouts
-------------	---------------------	---	--------------------------------------

### Wall Switches White

20A Double Pole Switch with Flex Outlet	<b>WPDP84FOW</b>	<b>WPDP84FOBW</b>	<b>WPDP84FOBKOW</b>
20A Double Pole Switch with LED Indicator & Flex Outlet	<b>WPDP84FONW</b>	<b>WPDP84FONBW</b>	<b>WPDP84FONBKOW</b>

### Wall Switches Grey

20A Double Pole Switch with Flex Outlet	<b>WPDP84FO</b>	<b>WPDP84FOB</b>	<b>WPDP84FOBKO</b>
20A Double Pole Switch with LED Indicator & Flex Outlet	<b>WPDP84FON</b>	<b>WPDP84FONB</b>	<b>WPDP84FONBKO</b>

## Metalclad Wall Switches (50A)

### Characteristics:

- Unique patented LOOP terminal to allow neutral looping at the switch.
- Complies with BS EN 60669-2-4.
- Capacity of each terminal 2 x 6.0mm<sup>2</sup> conductors.



WPDP50N

Description	Cat ref. Plate Only	Cat ref. With Backbox Without Knockouts	Cat ref. With Backbox With Knockouts
-------------	---------------------	---	--------------------------------------

### Wall Switches White

50A Double Pole Switch 1 Gang with LED Indicator	<b>WPDP50NW</b>	<b>WPDP50NBW</b>	<b>WPDP50NBKOW</b>
--	-----------------	------------------	--------------------

### Wall Switches Grey

50A Double Pole Switch 1 Gang with LED Indicator	<b>WPDP50N</b>	<b>WPDP50NB</b>	<b>WPDP50NBKO</b>
--	----------------	-----------------	-------------------