



WMCS11

## Light Switches

### Characteristics:

- Complies with BS EN 60669-1.
- 'X' rated - no need to de-rate for fluorescent loads.
- Earth terminal in base.
- Switch will operate at up to an angle of 45°.
- Pull cords 1.5m long.
- Capacity of each terminal: 2 x 1.5mm<sup>2</sup> conductors.

Description

Cat ref.

### 6A Ceiling Switch

1 Way

**WMCS11**

2 Way

**WMCS12**



WMCS3PIF

## Fan Isolator Switches

### Characteristics:

- Complies with BS EN 60669-2-4.
- Terminal capacity: 3 x 1.5mm<sup>2</sup>.
- Supplied with M3.5 x 30mm long fixing screws.

Description

Cat ref.

### 10A 3 Pole Ceiling Switch

Printed with Fan Symbol & 'Isolator'

**WMCS3PIF**

Printed 'Isolator'

**WMCS3PI**

Printed with Fan Symbol

**WMCS3PF**



WMCS50N

## Shower Switches

### Characteristics:

- Complies with BS EN 60669-2-4.
- Rated conditional short circuit current ( $I_{nc}$ ) 1500A tested with Hager **MTN150** 6kA B Curve MCB.
- Suitable for use with showers up to 11.5kW.
- Position of the contacts shown by flag indicator.
- Supplied with M3.5 x 30mm fixing screws.
- Capacity of each terminal: 1 x 16mm<sup>2</sup> conductors.

Description

Cat ref.

50A 2 Pole Isolating with LED Indicator

**WMCS50N**

## Accessories for Ceiling Switches

Description

Cat ref.

Single Spare Pull Cord

**PULLCORD**