

# ACCENT/DISPLAY SPECIFICATION

	ATOM		PLATINUM MINI						PLATINUM GLOSS						PLATINUM MATT						CARBON							
	LFR5**475D40	LFR5**450D27	LDP15W11*S40	LDP15W11*D40	LDP15W15*S40	LDP15W15*D40	LDP15W21*S40	LDP15W21*D40	LDP20W32GS40	LDP20W32GD40	LDP20W22GS40	LDP20W22GD40	LDP20W16GS40	LDP20W16GD40	LDP20W12GS40	LDP20W12GD40	LDP20W31GS40	LDP20W31GD40	LDP20W21GS40	LDP20W21GD40	LDP20W15GS40	LDP20W15GD40	LDP20W11GS40	LDP20W11GD40	LBDL8540	LBDL8540	LBDL6540	
PAGE NUMBER	51	51	52	52	52	52	52	52	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	54	56	56	57	
LENGTH / DIA (mm)	84	84	165	165	165	165	165	165	218	218	218	218	218	218	218	218	218	218	218	218	218	218	218	218	245	245	197	
WIDTH (mm)	N/A																											
HEIGHT/DEPTH (mm)	110	110	90	90	90	90	90	90	115	115	115	115	115	115	115	115	115	115	115	115	115	115	115	115	99	99	85	
WEIGHT (kg)	0.4	0.4	0.72	0.72	0.72	0.72	0.72	0.72	1.25	1.25	1.15	1.15	1.15	1.15	1.15	1.15	1.25	1.25	1.15	1.15	1.15	1.15	1.15	1.15	0.5	0.5	0.35	
L FIXING CENTRES (mm)	N/A																											
W FIXING CENTRES (mm)	N/A																											
CEILING CUT OUT (mm)	67	67	150	150	150	150	150	150	205	205	205	205	205	205	205	205	205	205	205	205	205	205	205	205	210	210	175	
LUMINAIRE LUMENS (Lm)	475	450	1050	1050	1500	1500	2050	2050	3200	3200	2200	2200	1600	1600	1200	1200	3050	3050	2050	2050	1500	1500	1100	1100	2000	2000	1500	
LUMINAIRE WATTAGE (W)	5.2	5.2	9	9	13	13	19	19	33	33	22	22	16	16	12	12	33	33	22	22	16	16	12	12	22	22	15	
EFFICACY Lm/W	91	87	117	117	115	115	108	108	97	97	98	98	100	100	100	100	92	92	93	93	94	94	92	92	91	91	100	
CCT (K)	4000	2700	4000																									
CRI	>80																											
UGR	N/A	N/A	≤16	≤16	≤17	≤17	≤18	≤18	≤21	≤21	≤20	≤20	≤19	≤19	≤18	≤18	≤21	≤21	≤20	≤20	≤19	≤19	≤18	≤18	N/A	N/A	N/A	
IP RATED	IP65	IP65	IP44																									
IK RATED	N/A																											
GLOW WIRE (°C)	N/A																											
RAL COLOUR	WH/PC/BS	WH/PC/BS	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016	9016
TEMP. RANGE (°C)	0 to +30	0 to +30	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	-20 to +40	
RATED LIFE (HR)	50,000																											
AMBIENT TEMP. RATED LIFE (HR)	25																											
L AT RATED LIFE (HR)	70																											
B AT RATED LIFE (HR)	50	50	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	50	50	50	
VOLTAGE RANGE	220-240V																											
FREQUENCY	50hz																											
EMERGENCY PACK CODE	N/A		LED3EP80-0J																									
WARRANTY (3 / 5 / 7 YEARS)	7 YEAR WARRANTY		5 YEAR WARRANTY																									