

## Connection Units

- Lockable fuse carrier for safety isolation
- Engraving available to order
- Neon versions available
- Captive fuse carrier
- Optional bottom flex outlet
- Twin earth terminals
- In compliance with BS 1363: Part 4
- 10-year guarantee

### Unswitched

- V12103\* 3A unswitched
- V1210P3\* 3A unswitched with neon
- V121013 13A unswitched
- V1210P13 13A unswitched with neon

### Switched

- V1211 13A DP switched
- V1212 13A DP switched with neon


### Back Boxes

Minimum recommended depth

	flush 25mm	dry lining 35mm	surface 25mm
1g	DB162	DB2540	V1221



V121013



V1210P13



V1211



V1212

## 20A Double Pole Switches

- Red flagged switch indicator
- Engraving available to order
- Neon versions available
- Twin brass earth terminals
- Optional flex outlet
- In compliance with BS EN 60669-1
- 10-year guarantee

### 20 Amp


- V1213 1 gang switch
- V1213WH\* 1 gang switch, engraved 'WATER HEATER'
- V1214 1 gang switch with neon
- V1214WH 1 gang switch with neon, engraved 'WATER HEATER'
- V1218P Dual immersion heater changeover switch with neon (marked 'SINK' and 'BATH')



V1213



V1213WH



V1214



V1214WH



V1218P

### Back Boxes

Minimum recommended depth

	flush 35mm	dry lining 35mm	surface 35mm
1g	DB164	DB2540	V1222

\*Special order product, minimum order quantity and lead time applies