

## Round Pin Socket Outlets

- Earth pin operated safety shutters
- In compliance with BS 546
- 10-year guarantee

### Unswitched

- V1330\* 2A unswitched
- V1331 5A unswitched
- V1332\* 15A unswitched



V1330



V1331



V1332

### Back Boxes

Minimum recommended depth


	flush 25mm	dry lining 35mm	surface 25mm
1g	DB162	DB2540	V1221

## Plate Switches

- All plate switches are X-rated and can be used for switching inductive or fluorescent loads without de-rating
- Optional cord outlet (V1247)
- In compliance with BS EN 60669-1
- 10-year guarantee

### 10 Amp


- V1202 1 gang 1-way
- V1203 1 gang 2-way
- V1204 2 gang 2-way
- V1205 3 gang 2-way
- V1244 4 gang 2-way
- V1245 6 gang 2-way
- V1246 Intermediate switch



V1203



V1204



V1244



V1249B



V1247

### 10 Amp Press

- V1249 Press Switch - marked 'PRESS'
- V1249B Press Switch - marked with bell symbol

### 10 Amp 3 Pole Fan Isolator

- V1247 3 pole fan isolator

### Back Boxes

Minimum recommended depth

	flush 16mm	dry lining 35mm	surface 16mm		flush 25mm	dry lining 35mm	surface 25mm
1-3g	DB152	DB2540	V1220/E	4-6g	DB163	DB2541	V1223

\*Special order product, minimum order quantity and lead time applies