

---

PRODUCT-DETAILS

# SPL10/10M

## 10M X SPL10/BLACK CONDUIT



---

### General Information

Extended Product Type	SPL10/10M
Product ID	7TCA296030R0037
EAN	5020963005558
Catalog Description	10M X SPL10/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 10mm, Outside Diameter 11.8mm, Inside Diameter 7.0mm, Static Bend Radius 40mm, Reel Length 10 Meters, PVC Covering with Galvanised Steel Core, Black

---

### Ordering

EAN	5020963005558
Customs Tariff Number	8307106000

---

### Dimensions

Product Net Weight	3.57 lb 1.619 kg
--------------------	---------------------

---

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	7.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1/4 in NC10
Number of Batteries	0
Outside Diameter	11.8 mm
Product Name	flexible metal conduit
Product Type	Oil Resistant Conduit
Radius	40 mm
UPC	786210245775

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL10/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL10/10M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

