

eRCBOs

DSE201 M series $\boxed{10000}$ AC $\boxed{\sim}$ type, B characteristic



DSE201 M ... A30

DSE201 M AC type, B characteristic

Function: protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contact and additional protection against direct contact ($I_{\Delta n} = 30 \text{ mA}$).

Application: commercial, industrial

Standard: IEC 61009-1; IEC 61009-2-2; BS EN 61009-1

$I_{cn} = 10\,000 \text{ A}$

| N. of poles | Rated residual current $I_{\Delta n}$ [mA] | Rated Current I_n [A] | Bbn 8012542 EAN | Order details | | Weight 1 piece [kg] | Pack unit pc. |
|-------------------------|--|-------------------------|-----------------|-----------------|-------------------|---------------------|---------------|
| | | | | Type code | Order code | | |
| B characteristic | | | | | | | |
| 1P+N | 10 | 6 | 938132 | 2CSR275051R0065 | DSE201 M B6 AC10 | 0.200 | 1 |
| | | 10 | 297734 | 2CSR275051R0105 | DSE201 M B10 AC10 | 0.200 | 1 |
| | | 16 | 373230 | 2CSR275051R0165 | DSE201 M B16 AC10 | 0.200 | 1 |
| | | 20 | 373131 | 2CSR275051R0205 | DSE201 M B20 AC10 | 0.200 | 1 |
| | | 25 | 077534 | 2CSR275051R0255 | DSE201 M B25 AC10 | 0.200 | 1 |
| | | 32 | 077435 | 2CSR275051R0325 | DSE201 M B32 AC10 | 0.200 | 1 |
| | | 40 | 077336 | 2CSR275051R0405 | DSE201 M B40 AC10 | 0.200 | 1 |
| | | 50 | 077237 | 2CSR275051R0505 | DSE201 M B50 AC10 | 0.200 | 1 |
| 1P+N | 30 | 6 | 076438 | 2CSR275051R1065 | DSE201 M B6 AC30 | 0.200 | 1 |
| | | 10 | 076339 | 2CSR275051R1105 | DSE201 M B10 AC30 | 0.200 | 1 |
| | | 16 | 076230 | 2CSR275051R1165 | DSE201 M B16 AC30 | 0.200 | 1 |
| | | 20 | 076131 | 2CSR275051R1205 | DSE201 M B20 AC30 | 0.200 | 1 |
| | | 25 | 076032 | 2CSR275051R1255 | DSE201 M B25 AC30 | 0.200 | 1 |
| | | 32 | 353430 | 2CSR275051R1325 | DSE201 M B32 AC30 | 0.200 | 1 |
| | | 40 | 353331 | 2CSR275051R1405 | DSE201 M B40 AC30 | 0.200 | 1 |
| | | 50 | 266334 | 2CSR275051R1505 | DSE201 M B50 AC30 | 0.200 | 1 |