

eRCBOs

DSE201 M series 10000 A  type, B characteristic



DSE201 M ... A30

DSE201 M A type, B characteristic

Function: protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contact and additional protection against direct contact ($I_{\Delta n} = 30$ mA).

Application: commercial, industrial

Standard: IEC 61009-1; IEC 61009-2-2; BS EN 61009-1

$I_{cn} = 10\ 000$ A

N. of poles	Rated residual current $I_{\Delta n}$ [mA]	Rated Current I_n [A]	Bbn 8012542 EAN	Order details		Weight 1 piece [kg]	Pack unit pc.
				Type code	Order code		
B characteristic							
1P+N	10	6	079231	2CSR275151R0065	DSE201 M B6 A10	0.200	1
		10	305033	2CSR275151R0105	DSE201 M B10 A10	0.200	1
		16	305132	2CSR275151R0165	DSE201 M B16 A10	0.200	1
		20	400233	2CSR275151R0205	DSE201 M B20 A10	0.200	1
		25	400035	2CSR275151R0255	DSE201 M B25 A10	0.200	1
		32	400134	2CSR275151R0325	DSE201 M B32 A10	0.200	1
		40	058830	2CSR275151R0405	DSE201 M B40 A10	0.200	1
		50	896531	2CSR275151R0505	DSE201 M B50 A10	0.200	1
1P+N	30	6	830832	2CSR275151R1065	DSE201 M B6 A30	0.200	1
		10	839835	2CSR275151R1105	DSE201 M B10 A30	0.200	1
		16	896739	2CSR275151R1165	DSE201 M B16 A30	0.200	1
		20	768432	2CSR275151R1205	DSE201 M B20 A30	0.200	1
		25	831136	2CSR275151R1255	DSE201 M B25 A30	0.200	1
		32	840138	2CSR275151R1325	DSE201 M B32 A30	0.200	1
		40	830733	2CSR275151R1405	DSE201 M B40 A30	0.200	1
		50	839736	2CSR275151R1505	DSE201 M B50 A30	0.200	1