

PRODUCT-DETAILS

SP12/BL/50M

50M X SP12/BLACK CONDUIT



General Information

Extended Product Type	SP12/BL/50M
Product ID	7TCA296020R0051
EAN	5020963000621
Catalog Description	50M X SP12/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 50 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963000621
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	16.31 lb 7.397 kg
--------------------	----------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	17 in 432 mm

Package Level 1 Height	16 in 406 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 2 Units	1 piece
Package Level 2 Width	17 in 432 mm
Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	16 in 406 mm
Package Level 3 Units	1 piece
Package Level 3 Height	17 in 432 mm
Package Level 3 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	10.3 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	5/16 in
Number of Batteries	0
Outside Diameter	14.0 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	30 mm
UPC	786210275413

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP12/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP12/BL/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

