

PRODUCT-DETAILS

SP16/BL/50M

50M X SP16/BLACK CONDUIT



General Information

Extended Product Type	SP16/BL/50M
Product ID	7TCA296020R0084
EAN	5020963000386
Catalog Description	50M X SP16/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 50 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963000386
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	24.36 lb 11.048 kg
--------------------	-----------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	17 in 432 mm

Package Level 1 Height	16 in 406 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 2 Units	10 piece
Package Level 2 Width	17 in 432 mm
Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	16 in 406 mm
Package Level 3 Units	10 piece
Package Level 3 Width	17 in 432 mm
Package Level 3 Height	16 in 406 mm
Package Level 3 Depth / Length	16 in 406 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	13.0 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	17.0 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	35 mm
UPC	786210247670

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP16/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP16/BL/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

