

PRODUCT-DETAILS

S10/50M

50M X S10 CONDUIT



General Information

Extended Product Type	S10/50M
Product ID	7TCA296010R0008
EAN	5020963003325
Catalog Description	50M X S10 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 10mm, Reel Length 50 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963003325
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	11.02 lb 4.998 kg
--------------------	----------------------

Container Information

Package Level 2 Units	4 piece
Package Level 2 Width	37 in 940 mm
Package Level 2 Height	17 in

	432 mm
Package Level 2 Depth / Length	17 in 432 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Material	Galvanized Steel
Nominal Size	1/4 in 10 mm
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210261119

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S10/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S10/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

