

PRODUCT-DETAILS

SPL63/10M

10M X SPL63/BLACK CONDUIT



General Information

Extended Product Type	SPL63/10M
Product ID	7TCA296030R0310
EAN	5020963002908
Catalog Description	10M X SPL63/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 63mm, Outside Diameter 59.7mm, Inside Diameter 51.6mm, Static Bend Radius 345mm, Reel Length 10 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963002908
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	40.79 lb 18.499 kg
--------------------	-----------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	51.6 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	2 in NC63
Number of Batteries	0
Outside Diameter	59.7 mm
Product Name	FLEX METAL CONDUIT
Product Type	Oil Resistant Conduit
Radius	345 mm
UPC	786210247304

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL63/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL63/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

