

PRODUCT-DETAILS

SP63/BL/25M

25M X SP63/BLACK CONDUIT



General Information

Extended Product Type	SP63/BL/25M
Product ID	7TCA296020R0312
EAN	5020963009235
Catalog Description	25M X SP63/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 63mm, Outside Diameter 64.5mm, Inside Diameter 57.5mm, Static Bend Radius 115mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Black

Ordering

EAN	5020963009235
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	72.5 lb 32.88 kg
--------------------	---------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	37 in 940 mm

Package Level 2 Height	30 in 762 mm
Package Level 2 Depth / Length	30 in 762 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	57.5 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	2 in
Number of Batteries	0
Outside Diameter	64.5 mm
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	115 mm
UPC	786210259406

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP63/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP63/BL/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

