

PRODUCT-DETAILS

SPL50/10M

10M X SPL50/BLACK CONDUIT



General Information

Extended Product Type	SPL50/10M
Product ID	7TCA296030R0289
EAN	5020963002885
Catalog Description	10M X SPL50/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 50mm, Outside Diameter 47.5mm, Inside Diameter 40.4mm, Static Bend Radius 240mm, Reel Length 10 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963002885
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	28.7 lb 13.016 kg
--------------------	----------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	40.4 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1-1/2 in NC50
Number of Batteries	0
Outside Diameter	47.5 mm
Product Name	flex metal conduit
Product Type	Oil Resistant Conduit
Radius	240 mm
UPC	786210247267

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL50/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL50/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

