

---

PRODUCT-DETAILS

# SPL16/E

# SPL16/M/INSERT



---

## General Information

Extended Product Type	SPL16/E
Product ID	7TCA296030R0082
EAN	5020963005718
Catalog Description	SPL16/M/INSERT
Long Description	Nickel Plated Brass Conduit Entry Gland, Nominal Conduit Size 16 Millimeters

---

## Ordering

EAN	5020963005718
Customs Tariff Number	7412200090

---

## Dimensions

Product Net Weight	.02 lb 9.07 g
--------------------	------------------

---

## Container Information

Package Level 1 Units	10 piece
Package Level 2 Units	1000 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in

	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

## Additional Information

Application	Cable Protection at Conduit Entry / Exit Point
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Conduit Terminator
Size	3/8 Inch
Special Functions	Very High UV Protection and High Degree of Mechanical Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -65 to +300 °C
UPC	786210245836

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL16/E
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL16/E

## Classifications

ETIM 6	EC000814 - Threaded bush
ETIM 7	EC000814 - Threaded bush
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

