

PRODUCT-DETAILS

SP25/25/C

UNTHREADED FITTING FOR SP25



General Information

Extended Product Type	SP25/25/C
Product ID	7TCA296020R0176
EAN	5020963003158
Catalog Description	UNTHREADED FITTING FOR SP25
Long Description	Nickel Plated Brass Smooth Entry Bushing, Hole Size 1.00 Inch

Ordering

EAN	5020963003158
Customs Tariff Number	7412200090

Dimensions

Product Net Weight	.08 lb 36.281 g
--------------------	--------------------

Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /
Length

1 in
25 mm

Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Smooth Entry Bushing
Size	3/4 Inch
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210249155

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP25/25/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP25/25/C

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

