

# Housemaster - Consumer Units

## Steel enclosures

### Steel Enclosure to BS EN 61439-3

- Supplied factory fitted with switch disconnector and/or RCD, specification as table. Unit comes complete with shrouded busbar, earth and neutral bars and installation instructions.
- Colour RAL7035 Steel
- Adaptable split load versions.



HSSL8+8C

Way Combinations		Incomer		Split Load		Part No	Product Hierarchy 4300001 Order Code
		Isolator	RCD	Isolator	RCD		
4	-	100A	-	-	-	HSMS4C	1SKB106142C4001
7	-	100A	-	-	-	HSMS7C	1SKB109142C4001
11	-	100A	-	-	-	HSMS11C	1SKB113142C4001
16	-	100A	-	-	-	HSMS16C	1SKB118142C4001
20	-	100A	-	-	-	HSMS20C	1SKB122142C4001
4	-	-	80A/30mA	-	-	HSRC4C	1SKB106142C6001
7	-	-	100A/30mA	-	-	HSRC7C	1SKB109142C6001
11	-	-	100A/30mA	-	-	HSRC11C	1SKB113142C6001
16	-	-	100A/30mA	-	-	HSRC16C	1SKB118142C6001
20	-	-	100A/30mA	-	-	HSRC20C	1SKB122142C6001
4+4	3+5, 2+6	-	-	100A	80A/30mA	HSSL4+4C	1SKB113142C8001
6+6	4+8, 5+7	-	-	100A	80A/30mA	HSSL6+6C	1SKB118142C8001
8+8	7+9, 9+7	-	-	100A	80A/30mA	HSSL8+8C	1SKB122142C8001
4+4	-	100A	80A/30mA	-	63A/30mA	HSSE4186C	1SKB113142C8501
6+6	-	100A	80A/30mA	-	63A/30mA	HSSE6186C	1SKB118142C8501
8+8	-	100A	80A/30mA	-	63A/30mA	HSSE8186C	1SKB122142C8501

### Dimensions

Part No	Height mm	Width mm	Depth mm
HSMS4C - HSRC4C	256	155	110
HSMS7C - HSRC7C		210	
HSMS11C - HSRC11C - HSSL4+4C - HSSE4186C		282	
HSMS16C - HSRC16C - HSSL6+6C - HSSE6186C		368	
HSMS20C - HSRC20C - HSSL8+8C - HSSE8186C		440	