

PRODUCT-DETAILS

# SPL12/50M

## 50M X SPL12/BLACK CONDUIT



### General Information

Extended Product Type	SPL12/50M
Product ID	7TCA296030R0057
EAN	5020963000850
Catalog Description	50M X SPL12/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.2mm, Inside Diameter 10.0mm, Static Bend Radius 45mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Black

### Ordering

EAN	5020963000850
Customs Tariff Number	8307106000

### Dimensions

Product Net Weight	24.25 lb 10.998 kg
--------------------	-----------------------

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	9.5 in 241 mm

Package Level 2 Height	25 in 635 mm
Package Level 2 Depth / Length	28 in 711 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	10.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	5/16 in NC12
Number of Batteries	0
Outside Diameter	14.2 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	45 mm
UPC	786210274881

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL12/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL12/50M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

