

PRODUCT-DETAILS

# SPB25/M25/A

## PLAIN MALE BRASS ADPT IP54 NC25 M32



### General Information

Extended Product Type	SPB25/M25/A
Product ID	7TCA296040R0140
EAN	5020963004476
Catalog Description	PLAIN MALE BRASS ADPT IP54 NC25 M32
Long Description	Nickel Plated Brass Straight Fitting with Fixed External Thread, Nominal Conduit Size 25 Millimeters, IP54 Rating, Metric Thread Size M25

### Ordering

EAN	5020963004476
Customs Tariff Number	7412200035

### Dimensions

Product Net Weight	.14 lb 63.492 g
--------------------	--------------------

### Container Information

Package Level 1 Units	10 piece
Package Level 2 Units	200 piece
Package Level 2 Width	14 in 356 mm

Package Level 2 Height	6 in 152 mm
Package Level 2 Depth / Length	14 in 356 mm

---

### Additional Information

Application	For Insertion into Threaded Entries or Knockout to Connect Conduit
Brand / Label	Adaptaflex
Cable Entry Position	M25 Thread
Color	Metallic
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Conduit Fitting with Metric Threads
Size	3/4 Inch
Surface Finishing	Nickel Plated
UPC	786210245263

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPB25/M25/A
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPB25/M25/A

---

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

