

PRODUCT-DETAILS

# SP25/BL/50M

## 50M X SP25/BLACK CONDUIT



### General Information

Extended Product Type	SP25/BL/50M
Product ID	7TCA296020R0186
EAN	5020963000133
Catalog Description	50M X SP25/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 50 Meters, PVC Jacket with Galvanised Steel Core, Black

### Ordering

EAN	5020963000133
Customs Tariff Number	8307106000

### Dimensions

Product Net Weight	43 lb 19.501 kg
--------------------	--------------------

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	36 in 914 mm

Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

---

### Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	21.4 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	55 mm
UPC	786210249087

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP25/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP25/BL/50M

---

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

