

PRODUCT-DETAILS

# SP20/20/C

## UNTHREADED FITTING FOR SP20



### General Information

Extended Product Type	SP20/20/C
Product ID	7TCA296020R0129
EAN	5020963001055
Catalog Description	UNTHREADED FITTING FOR SP20
Long Description	Nickel Plated Brass Smooth Entry Bushing, Nominal Conduit Size 20 Millimeters, Hole Size 0.78 Inch

### Ordering

EAN	5020963001055
Customs Tariff Number	7412200045

### Dimensions

Product Net Weight	.05 lb 22.676 g
--------------------	--------------------

### Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in

	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	UNTHREADED BRASS FITTING FOR CONDUIT
Product Type	Smooth Entry Bushing
Size	1/2 Inch
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210259277

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP20/20/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP20/20/C

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

