

PRODUCT-DETAILS

S50/25M

25M X S50 CONDUIT



General Information

Extended Product Type	S50/25M
Product ID	7TCA296010R0156
EAN	5020963003684
Catalog Description	25M X S50 CONDUIT
Long Description	Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 50mm, Outside Diameter 53.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 25 Meters, Galvanised Steel General Purpose

Ordering

EAN	5020963003684
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	53.96 lb 24.472 kg
--------------------	-----------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Light Industrial, Buildings
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	48.4 mm
Material	Galvanized Steel
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	53.0 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	90 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210251608

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	S50/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	S50/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

