

PRODUCT-DETAILS

SP75/75/C

SP75 C TYPE



General Information

Extended Product Type	SP75/75/C
Product ID	7TCA296020R0334
EAN	5020963016882
Catalog Description	SP75 C TYPE
Long Description	Nickel Plated Brass Smooth Entry Bushing, Nominal Conduit Size 75 Millimeters, Hole Size 2.95 Inch

Ordering

EAN	5020963016882
Customs Tariff Number	7412200035

Dimensions

Product Net Weight	.66 lb 299.32 g
--------------------	--------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in

	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	For Locking Conduit Into Plain Holes in Enclosures
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Smooth Entry Bushing
Size	2-1/2 Inch
Special Functions	Very High UV Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -50 to +350 °C
UPC	786210249377

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP75/75/C
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP75/75/C

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

