

PRODUCT-DETAILS

# SP32/BL/25M

## 25M X SP32/BLACK CONDUIT



### General Information

Extended Product Type	SP32/BL/25M
Product ID	7TCA296020R0227
EAN	5020963000140
Catalog Description	25M X SP32/BLACK CONDUIT
Long Description	Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 32mm, Outside Diameter 34.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Black

### Ordering

EAN	5020963000140
Customs Tariff Number	8307106000

### Dimensions

Product Net Weight	33.74 lb 15.302 kg
--------------------	-----------------------

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	17 in 432 mm

Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	16 in 406 mm

---

### Additional Information

Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	28.1 mm
Material	Galvanized Steel Core with PVC Jacket
Nominal Size	1 in
Number of Batteries	0
Outside Diameter	34.0 mm
Product Name	flex metal conduit
Product Type	High Flexibility Conduit
Radius	60 mm
UPC	786210249162

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SP32/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SP32/BL/25M

---

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

