## Knightsbridge

## DATASHEET



## GDM005MB

20AX intermediate grid module - matt black

www.mlaccessories.co.uk

DESCRIPTION20AX intermediate grid module - matt blackNET WEIGHT (KG)0.027FINISHMatt BlackDIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 7 Recessed Depth - 18.7MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	MLA PART CODE	GDM005MB
FINISHMatt BlackDIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 7 Recessed Depth - 18.7MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	DESCRIPTION	20AX intermediate grid module - matt black
DIMENSIONS (MM)Height - 56.3 Width - 24.8 Projection - 7 Recessed Depth - 18.7MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	NET WEIGHT (KG)	0.027
DIMENSIONS (MM)Width - 24.8 Projection - 7 Recessed Depth - 18.7MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	FINISH	Matt Black
CONSTRUCTIONConstruction - ABS Construction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	DIMENSIONS (MM)	Width - 24.8 Projection - 7
CONSTRUCTIONConstruction 2 - & steelIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	MINIMUM MOUNTING BOX DEPTH	35mm
INPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	CONSTRUCTION	
SWITCH FUNCTIONIntermediateLOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	IP RATING	IP20
LOAD/MAX. LOAD20AXTERMINAL CAPACITY3 x 2.5mm² or 2 x 4.0mm²WARRANTY25year(s)	INPUT VOLTAGE	230V 50Hz
TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm²   WARRANTY 25year(s)	SWITCH FUNCTION	Intermediate
WARRANTY 25year(s)	LOAD/MAX. LOAD	20AX
	TERMINAL CAPACITY	3 x 2.5mm <sup>2</sup> or 2 x 4.0mm <sup>2</sup>
	WARRANTY	25year(s)
MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1	MANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5056270801156	EAN	5056270801156

Date Created: 01/03/2023 14:10





