



RCBOs With Solid Neutral Single Pole 6kA TYPE AC

B CURVE
ONE MODULE

PART NO.	DESCRIPTION
H7932s	6A 230V, 30mA Tripping Current
H7933s	10A 230V, 30mA Tripping Current
H7934s	16A 230V, 30mA Tripping Current
H7935s	20A 230V, 30mA Tripping Current
H6310s	32A 230V, 10mA Tripping Current
H7936s	32A 230V, 30mA Tripping Current
H7937s	40A 230V, 30mA Tripping Current
H7938s	45A 230V, 30mA Tripping Current
H7939s	50A 230V, 30mA Tripping Current



C CURVE
ONE MODULE

PART NO.	DESCRIPTION
H8932s	6A 230V, 30mA Tripping Current
H8933s	10A 230V, 30mA Tripping Current
H8934s	16A 230V, 30mA Tripping Current
H8935s	20A 230V, 30mA Tripping Current
H8936s	32A 230V, 30mA Tripping Current
H8937s	40A 230V, 30mA Tripping Current
H8938s	50A 230V, 30mA Tripping Current



RCBOs With Solid Neutral Single Pole 6kA TYPE A

B CURVE
ONE MODULE

PART NO.	DESCRIPTION
H6832s	6A 230V, 30mA Tripping Current
H6833s	10A 230V, 30mA Tripping Current
H6834s	16A 230V, 30mA Tripping Current
H6835s	20A 230V, 30mA Tripping Current
H6836s	32A 230V, 30mA Tripping Current
H6837s	40A 230V, 30mA Tripping Current
H6838s	50A 230V, 30mA Tripping Current

Suitable for installation in MK Sentry Consumer Units.
Positive contact status indication.

DIMENSIONS:	CABLE CAPACITY:	SHORT CIRCUIT BREAKING CAPACITY:
114 x 18 x 79mm	Live In 25mm ² Neutral In 25mm ² Live Out 10mm ² Neutral Out 10mm ²	6KA

