



PRW115

PRW119/120/124/125

PRW121/122/126/127

Twin outlets are 2 separate sockets and not internally linked together.

RJ11 Telephone Outlet - PC

PRW115 Single RJ11 (Irish/US) Outlet

Telephone Outlets - Urea

PRW119 Single Telephone Outlet - Master

PRW122 Twin Telephone Outlet - Master

PRW124 Single Telephone Outlet - Secondary

PRW127 Twin Telephone Outlet - Secondary

Telephone Outlets - PC

PRW120 Single Telephone Outlet - Master

PRW121 Twin Telephone Outlet - Master

PRW125 Single Telephone Outlet - Secondary

PRW126 Twin Telephone Outlet - Secondary

Back Box Depth: 16mm Minimum RJ11: 35mm Minimum **Termination Type:** IDC
Dimensions: Urea: (86mm x 86mm x 11mm), PC: (85mm x 85mm x 8mm)



PRW065

PRW066

PRW156



PRW170



PRW157



PRW158



PRW159

Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Non-Isolated Coaxial Outlets (Unshielded)

PRW065 Single Coaxial Outlet

PRW066 Twin Coaxial Outlet

Isolated Coaxial Outlets (Unshielded)

PRW158 Single Isolated Coaxial Outlet

PRW159 Twin Isolated Coaxial Outlet

Satellite Outlets (Unshielded)

PRW156 Non-Isolated Single Satellite Outlet

PRW170 Non-Isolated Satellite & Non-Isolated Coaxial Outlet

PRW157 Isolated Satellite & Isolated Coaxial Outlet

Back Box Depth: 16mm Minimum
Dimensions: 1 Gang: (86mm x 86mm x 11mm), 2 Gang: (146mm x 86mm x 11mm)