



CMA612



CMA618



MINIGRID®

The furnished plate shown here contains a selection of both single and twin width Minigrid™ modules. The yoke 'GR101' is supplied enabling Minigrid™ modules to be mounted prior to assembling the front plate.

MINIGRID® GR101 yokes supplied complete with the frontplate. Also available as a spare. For the complete range of Minigrid™ modules, see the dedicated Minigrid™ section, page j18.

2 Tier Unfurnished Plates - MiniGrid™

CMA612 2 Tier MiniGrid™ Unfurnished Plate & Yokes - 12 Apertures - Mode®

3 Tier Unfurnished Plates - MiniGrid™

CMA618 3 Tier MiniGrid™ Unfurnished Plate & Yokes - 18 Apertures - Mode®

Decorative Finished Deco® Victorian Plate Finishes Also Available.
Switch modules interchangeable with Minigrid™ modules in Polar™ white (PW) finish.

Back Box Depth: 47mm Minimum Cable Size: Dependant on module used
Dimensions: 12 Module: (146mm x 153mm x 9.5mm) 18 Module: (143mm x 214mm x 9.5mm)



WA512



WA518

MINIGRID® Galvanised steel back boxes supplied for flush mounting of the large Minigrid™ plates.

Galvanised Steel Back Boxes

WA512 2 Tier 47mm Deep K.O. Box

WA518 3 Tier 47mm Deep K.O. Box

Dimensions: WA512: 137mm x 137mm WA518: 137mm x 197mm