



CMA215

PRW217



PRW215



PRW218

**45A Cooker Connection Plates**

- CMA215** 45A 1 Gang Cooker Connection Plate
- PRW215** 45A 1 Gang Cooker Connection Plate
- PRW217** 45A Easyfit Dual Appliance Outlet Plate

UK Design Registration No. 3015175

**Pattress Box for PRW217 - Urea**

- PRW218** 35mm Deep Pattress Box For Use With PRW217

Standards: 215/217: BS 5733  
 Back Box Depth: 215: 35mm Minimum 217: 25mm Minimum  
 Cable Size: 215: 2 x 10mm<sup>2</sup> 217: 1 X 10mm<sup>2</sup>  
 Dimensions: 215: 84mm x 84mm x 23mm 217: 84mm x 130mm x 27mm



DB700

DB750

DB981



DB701



DB751



DB790

Fuse Manufacturer				
Rating	Bussmann	Lawson	MEM	GE
40A	40KR85	ME40	404R	RHF40
45A	45KR85	ME45	454R	-
50A	50KR85	ME50	504R	RHF50
60A	60KR85	ME60	604R	RHF60
70A	70KR85	ME70	-	-
80A	80KR85	ME80	804R	RHF80
100A	100KR85	ME100	-	-

80A and 100A variants are supplied with an 80A Bussmann fuse as standard. However the following fuses will fit:

**Fused Main Switch**

- DB700** 80A Fused Main Switch (80A HRC Fuse Fitted)
- DB701** 80A Fused Main Switch (80A HRC Fuse Fitted) - Lockable
- DB750** 100A Fused Main Switch (80A HRC Fuse Fitted)
- DB751** 100A Fused Main Switch (80A HRC Fuse Fitted) - Lockable
- DB790** Metal Enclosure for Fused Main Switch (DB700/701)
- DB791** Metal Enclosure for Fused Main Switch (DB750/751)
- DB981** Elongated Cable Shroud (Packaged Individually)

Standards: BS EN 60947  
 Cable Size: DB700/DB701: 1 x 25mm<sup>2</sup> DB750/DB751: 1 x 35mm<sup>2</sup> Dimensions: DB700/DB701: 120mm x 80mm x 55mm  
 DB750/DB751: 133mm x 101mm x 60mm DB981: 80mm x 90mm x 45mm