




CT105C



CT105F



CT105M



CT115C




CT115F

Time saving levers

Simply push lever down, offer stripped conductor into the terminal & then release the lever, ensuring the cable cannot easily be pulled out.



CT205C



CT205F



CT205M



CT215C



CT215F

Time saving levers

Simply push lever down, offer stripped conductor into the terminal & then release the lever, ensuring the cable cannot easily be pulled out.



3 Pole Flow™ Connectors

- CT105C** 250V 20A 3 Pole Complete Fast-Fit Connector (CT105M & CT105F)
- CT105F** 250V 20A 3 Pole Female Fast-Fit Connector
- CT105M** 250V 20A 3 Pole Male Fast-Fit Connector
- CT115C** 250V 20A 3 Pole Complete Fast-Fit Connector With Loop (CT105M & CT115F)
- CT115F** 250V 20A 3 Pole Female Fast-Fit Connector With Loop

Standards: BS EN 61535
Cable Size: 2.5mm² Max **Current Rating:** 20A
Dimensions: CT105C: 142mm x 36mm x 24mm CT115C: 142mm x 51mm x 24mm CT105F: 79mm x 36mm x 23mm
 CT105M: 79mm x 36mm x 24mm CT115F: 79mm x 51mm x 23mm

4 Pole Flow™ Connectors

- CT205C** 250V 20A 4 Pole Complete Fast-Fit Connector (CT205M & CT205F)
- CT205F** 250V 20A 4 Pole Female Fast-Fit Connector
- CT205M** 250V 20A 4 Pole Male Fast-Fit Connector
- CT215C** 250V 20A 4 Pole Complete Fast-Fit Connector With Loop (CT205M & CT215F)
- CT215F** 250V 20A 4 Pole Female Fast-Fit Connector With Loop

Standards: BS EN 61535
Cable Size: 2.5mm² Max **Current Rating:** 20A
Dimensions: CT205C: 142mm x 47mm x 24mm CT215C: 142mm x 62mm x 24mm CT205F: 79mm x 47mm x 23mm
 CT205M: 79mm x 47mm x 24mm CT215F: 79mm x 62mm x 23mm