



MD001WH



MD001  
(Back)



MD002BR



MD002  
(Back)

Conventional moulded 1 way, 2 way and intermediate switch modules can be used in all Click® accessories, Polar™ and Mode® moulded and metal ranges.

**10AX 1 Way Switch Modules**

- MD001BK 1 Way Switch Module - Black
- MD001PW 1 Way Switch Module - Polar™ White
- MD001WH 1 Way Switch Module - Click® White

**10AX 2 Way Switch Modules**

- MD002BK 2 Way Switch Module - Black
- MD002PW 2 Way Switch Module - Polar™ White
- MD002WH 2 Way Switch Module - Click® White
- MD002RD 2 Way Switch Module - Red

**Ingot 10AX 2 Way Switch Modules**

- MD002AB Ingot 2 Way Switch Module - Antique Brass
- MD002BN Ingot 2 Way Switch Module - Black Nickel
- MD002BR Ingot 2 Way Switch Module - Polished Brass
- MD002BS Ingot 2 Way Switch Module - Brushed Stainless
- MD002CH Ingot 2 Way Switch Module - Polished Chrome
- MD002PN Ingot 2 Way Switch Module - Pearl Nickel
- MD002SB Ingot 2 Way Switch Module - Satin Brass
- MD002SC Ingot 2 Way Switch Module - Satin Chrome
- MD002SS Ingot 2 Way Switch Module - Stainless Steel

Standards: BS EN 60669  
Module Depth: 20mm Minimum Cable Size: 4 x 1.5mm<sup>2</sup> / 2 x 2.5mm<sup>2</sup> / 1 x 6mm<sup>2</sup> Maximum



MD028PW



MD028AB



MD028BR



MD028SS



MD028  
(Back)



MD028BS



MD028CH



MD028SB

Conventional moulded 1 way, 2 way and intermediate switch modules can be used in all Click® accessories, Polar™ and Mode® moulded and metal ranges.

**10AX Intermediate Switch Modules**

- MD028BK Intermediate Switch Module - Black
- MD028PW Intermediate Switch Module - Polar™ White
- MD028WH Intermediate Switch Module - Click® White

**Ingot 10AX Intermediate Switch Modules**

- MD028AB Intermediate Switch Module - Antique Brass
- MD028BN Intermediate Switch Module - Black Nickel
- MD028BR Intermediate Switch Module - Polished Brass
- MD028BS Intermediate Switch Module - Brushed Stainless
- MD028CH Intermediate Switch Module - Polished Chrome
- MD028PN Intermediate Switch Module - Pearl Nickel
- MD028SB Intermediate Switch Module - Satin Brass
- MD028SC Intermediate Switch Module - Satin Chrome
- MD028SS Intermediate Switch Module - Stainless Steel

Standards: BS EN 60669  
Module Depth: 20mm Minimum Cable Size: 4 x 1.5mm<sup>2</sup> / 2 x 2.5mm<sup>2</sup> / 1 x 6mm<sup>2</sup> Maximum