



CMA022

CMA023

CMA044



CMA046

CMA660

CMA622



CMA623

CMA040

CMA042

**20A Control Switches With Optional Flex Outlet Through The Bottom**

- CMA022 20A DP Switch
- CMA023 20A DP Switch With Neon
- CMA044 20A DP 'Water Heater' Switch With Flex Outlet
- CMA046 20A DP 'Water Heater' Switch With Flex Outlet & Neon

**20A Control Switch Without Flex Outlet**

- CMA622 20A DP Switch
- CMA623 20A DP Switch With Neon
- CMA040 20A DP 'Water Heater' Switch
- CMA042 20A DP 'Water Heater' Switch With Neon

**Lockable Switch**

- CMA660 20A Double Pole Key Lockable Switch

Standards: BS EN 60669 660: BS 1363-2, BS EN 60669-1  
 Back Box Depth: 25mm Minimum 660: 35mm Minimum Cable Size: 4 x 2.5mm<sup>2</sup> 660: 3 x 2.5mm<sup>2</sup>, 2 x 4mm<sup>2</sup>  
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm)



CMA200

CMA201



CMA204

CMA202



CMA205

CMA203

**45A Switches**

- CMA200 45A 1 Gang DP Switch
- CMA201 45A 1 Gang DP Switch With Neon
- CMA202 45A 2 Gang DP Switch
- CMA203 45A 2 Gang DP Switch With Neon

**Cooker Control Units**

- CMA204 45A 2 Gang DP Switch With 13A DP Switched Socket
- CMA205 45A 2 Gang DP Switch With 13A DP Switched Socket & Neons

Standards: BS 4177, BS EN 60669  
 Back Box Depth: 35mm Minimum Cable Size: 45A: 1 x 16mm<sup>2</sup>  
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm), 2 Gang: (146mm x 86mm x 9.5mm)