



401 402 403



404



406 426



140 152



153 154

MINIGRID® For MiniGrid™ modules - see page j18

Unfurnished Plates - MiniGrid™

- 401 1 Gang MiniGrid™ Unfurnished Plate - 1 Aperture
- 402 1 Gang MiniGrid™ Unfurnished Plate - 2 Apertures
- 403 1 Gang MiniGrid™ Unfurnished Plate - 3 Apertures
- 404 2 Gang MiniGrid™ Unfurnished Plate - 2 x 2 Apertures
- 406 2 Gang MiniGrid™ Unfurnished Plate - 2 x 3 Apertures
- 426 2 Gang MiniGrid™ Unfurnished Plate - 6 In-Line Apertures

Dimensions: 1 Gang: (88mm x 88mm x 1.3mm*), 2 Gang: (146mm x 88mm x 1.3mm*) *Excluding gasket

Understanding the code:
 FP - Plate Style BN - Plate Finish 411 - Product No. BK - Insert Colour.
 BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel

MINIGRID® Interchangeable modules available on page j36

Dimmer Switches

- 140 1 Gang 2 Way 400Va Dimmer Switch
- 152 2 Gang 2 Way 400Va Dimmer Switch
- 153 3 Gang 2 Way 400Va Dimmer Switch
- 154 4 Gang 2 Way 400Va Dimmer Switch

We recommend the use of branded halogen lamps with all Define® dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. These dimmer switches have not been designed for use with LED lamps. However, they may be suitable for some good quality LED lamps. For further information please contact the Click® technical support team.

Standards: BS EN 60669, BS EN 55015 Type: Leading Edge
 Back Box Depth: 35mm Minimum Cable Size: 2 x 1.5mm²
 Dimensions: 1 Gang: (88mm x 88mm x 1.3mm*), 2 Gang: (146mm x 88mm x 1.3mm*) *Excluding gasket

Understanding the code:
 FP - Plate Style BN - Plate Finish 411 - Product No. Please note: Supplied with both black & white gaskets (BN supplied with black gaskets only).
 BS Brushed Stainless, BN Black Nickel, PN Pearl Nickel, CH Polished Chrome and SS Stainless Steel