

## SHOWER WATER HEATERS FOR ONE DRAW-OFF POINT



Model	EB 15 SL comfort	
- Type	EB 15 SL	
- Part no.	222205	222206
Application		
- Nominal capacity	15	
- For one / several draw-off points	• / -	• / -
- Mounting form		
- Oversink unit	•	•
- Undersink unit	-	-
Connection details		
- Type	Non-pressurised (open)	
- Permiss. op. pressure MPa/bar	-	
- Mixed water volume of 40 °C <sup>1)</sup>	28	
- Stand-by power consumption at 65 °C / 24 h kWh	-	-
- Connected load <sup>2)</sup> kW	2	3.3
- Voltage	1/N/PE ~ 230 V	
- Protection level	IP 24 (splash-proof)	
- Test symbols	VDE / CE	
Equipment level		
- Copper inner cylinder	-	-
- Plastic inner cylinder	•	•
- Temperature range °C	35 to 85	
- Temperature limit adjustable to °C	-	-
- Economy option Eco °C	-	-
- Colour	White	
Weight and dimensions		
- Dimensions (HxWxD <sup>3)</sup> mm	601x316x295	
- Wet weight kg	21.7	
Accessories		
- Taps	Non-pressurised taps	
- Safety valves	-	-

## SMALL WATER HEATERS FOR SEVERAL DRAW-OFF POINTS



SHU 5-10 SLi comfort		SH 10-15 SLi comfort		
SHU 5 SLi	SHU 10 SLi	SH 10 SLi	SH 15 SLi	
222151	222199	222181	222211	222209
Application				
- Nominal capacity	5	10	10	15
- For one / several draw-off points	• / •	• / •	• / •	• / •
- Mounting form				
- Oversink unit	-	-	•	•
- Undersink unit	•	•	-	-
Connection details				
- Type	Pressure tested (sealed)		Pressure tested (sealed)	
- Permiss. op. pressure MPa/bar	0.7 / 7		0.7 / 7	
- Mixed water volume of 40 °C <sup>1)</sup>	10	19	19	28
- Stand-by power consumption at 65 °C / 24 h kWh	0.31	0.36	0.35	0.41
- Connected load <sup>2)</sup> kW	2.0		2.0	3.3
- Voltage	1/N/PE ~ 230 V		1/N/PE ~ 230 V	
- Protection level	IP 24 (splash-proof)		IP 24 (splash-proof)	
- Test symbols	VDE / CE		VDE / CE	
Equipment level				
- Copper inner cylinder	•	•	•	•
- Plastic inner cylinder	-	-	-	-
- Temperature range °C	35 to 82		35 to 82	
- Temperature limit adjustable to °C	38, 45, 55, 65		38, 45, 55, 65	
- Economy option Eco °C	60		60	
- Colour	White		White	
Weight and dimensions				
- Dimensions (HxWxD <sup>3)</sup> mm	421x263x230	503x295x275	503x295x275	601x316x295
- Wet weight kg	10.2	18.0	18.1	25.9
Accessories				
- Taps	-	-	-	-
- Safety valves	SVMT		KV 307, KV 40	

### Key

• Available, or yes.

<sup>1)</sup> The mixed water volume has a service temperature of 40 °C which is based on a cold water temperature of 15 °C and a cylinder water temperature of 65 °C (with respect to the operational state).

<sup>2)</sup> Regulations vary according to local power supply company; to be connected only by a qualified electrician – except for units which are delivered ready to plug in.

<sup>3)</sup> Including water supply connector (excl. taps/valves).