

# BIS RapidRail® Connector 90°

(G 35 05)

to make BIS RapidRail® fabrications



## Features and benefits

- connector with pre-assembled BIS RapidRail® Slide nut(s)
- to make rail fabrications
- suitable for WMO, 1, 15, 2, 30, 35
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- zinc plated

Part No.	Model	a (°)	T (max.) (Nm)	For Rail	Fa,z (N)	Fa,x (N)	RAL	Pack 1
658 4 001	Long / long	90°	15.0	WMO - 35	1,562	720	RAL <sup>1</sup>	25
658 4 002	Short / long	90°	15.0	WMO - 35	1,336	448	RAL <sup>1</sup>	25
658 4 003	Short / short	90°	15.0	WMO - 35	1,336	448	RAL <sup>1</sup>	25
658 4 011	Long / long	90°	15.0	WMO - 35	1,562	720	RAL <sup>1</sup>	25

*RAL<sup>1</sup> = tested, certified and monitored by a third party according to RAL-GZ 655/D in combination with Rail WM1, 2, 15 and 30.  
For detailed technical information about our RAL marked products, please see the RAL datasheet in our web catalogue.*



RAL-GZ 655/D  
Cert.Nr. 2012-09

