

Outdoor timers & switches

Outdoor Illuminated Touch timer



4
Outdoor Illuminated Touch Timer
Outdoor Timers & Switches

Outdoor Illuminated Touch Timer - Outdoor timers & switches

The Outdoor Illuminated Touch Timer offers superb functionality and energy saving features with a subtle touch activation for a wide range of outdoor use.

The unit when used in outdoor environments offers increased reliability as a non-mechanical electronic unit. Knockouts on five faces, nylon washers, mounting screws and seal screw covers. Variable timing selection and a backlit blue neon indicator ring are both part of this feature-packed device. It is also suitable for multi-way applications in slave switch options with the 2 wire and 3 wire master devices.

Key Features

- 16A any load type
- Time cancellation functions
- Re-trigger function
- Blue locator ring
- One minute countdown LED indicator
- Last minute indicator
- Can be interlinked with any Elkay outdoor slave switches switching (Only one master per circuit)
- Timer settings from 2 mins to 2 hours

560A-1

- 3 wire (Live, switch live and neutral required)

Typical applications:

- Commonly used for outdoor patio or infrared heaters and where there is a neutral, to control all load types of lighting.

560A-3

- 2 wire (Live and switch live required)
- A 24 hour uninterrupted supply is required.

Typical applications:

- Commonly used to control all types of lighting such as LEDs and incandescent/fluorescent lighting

560A-5

- 3 core - Live, switch live and trigger required

Typical applications:

- For general purpose loads including resistive loads and incandescent/fluorescent lighting
- Slaves must be used when more than one switch is required in circuit and must be wired in three core to an Elkay master timer from the illuminated range. Only one master per circuit. All other switches must be slaves.

Outdoor Illuminated PIR Timer - Technical specification

| Part No. | Type | Configuration | Finish | Rating | GID |
|-----------|----------------------------------------|-----------------------------|--------|----------|-----------------|
| 560A-1*** | Outdoor Illuminated Touch Timer Master | 3 Wire | White | 16A-240V | 7TCA299010R0065 |
| 560A-3*** | Outdoor Illuminated Touch Timer Master | 2 Wire* (for lighting only) | White | 16A-240V | 7TCA299010R0068 |
| 560A-5 | Outdoor Illuminated Touch Slave Switch | 3 Core** | White | 16A-240V | 7TCA299010R0070 |

*PFCC-1 Capacitor will often be required when switching certain types of load - see Section 3/15 for full details or contact Elkay Technical

Slaves must be used with illuminated range and connected with 3 Core cables to Master unit. *Slave unit required for multiway switching See Technical Section 6/4 & 6/6 for wiring diagrams