



# MP, MP90 & T system

IP40

IP67

**Construction:** Nylon compression fittings.

**Colour:** Black.

**MP** fitting with nylon retaining clip provides a pull off strength of 20kg with FPY20 and 15kg with FPYL20 and IP40.

**MPS** fitting with a neoprene sealing ring provides a pull off strength of 15kg with FPY20 and 10kg with FPYL20 and IP67.



## Fittings

MP	MPS	MP90	MPS90	T	TS
<b>straight external thread</b> Straight nylon compression fitting external thread including locknut.	<b>straight external thread</b> Straight nylon compression fitting, with seal, external thread including locknut.	<b>90° elbow external thread</b> 90° elbow nylon compression fitting external thread including locknut.	<b>90° elbow external thread</b> 90° elbow nylon compression fitting, with seal, external thread including locknut.	<b>T Piece fitting</b> T piece nylon compression fitting.	<b>T Piece fitting with seals</b> T piece nylon compression fitting, with seals.
IP40	IP67	IP40	IP67	IP40	IP67



MP shown



MP shown



IP40  
T shown

Ext Metric

Ext Metric

Ext Metric

Ext Metric

T Piece

T Piece

european (NW) sizes  
nominal size (mm)  
OD mm

						7	10	10.0
						8	11	11.5
MP-12-M16	MPS-12-M16			T12X12X12	TS12X12X12	10	13	13.0
MP-16-M16	MPS-16-M16	MP90-16-M16	MPS90-16-M16	T16X16X16	TS16X16X16	12	16	15.8
MP-16-M20	MPS-16-M20	MP90-16-M20	MPS90-16-M20			12	16	
						14	18	18.5
MP-20-M20	MPS-20-M20	MP90-20-M20	MPS90-20-M20	T20X20X20	TS20X20X20	17	21	21.2
MP-25-M25	MPS-25-M25	MP90-25-M25	MPS90-25-M25	T25X25X25	TS25X25X25	22	25	25.4
MP-28-M25	MPS-28-M25	MP90-28-M25	MPS90-28-M25			23	28	28.5
MP-32-M32	MPS-32-M32	MP90-32-M32	MPS90-32-M32			29	34	34.5
MP-40-M40		MP90-40-M40				36	42	42.5
MP-50-M50						48	54	54.5

## Standards



BS EN IEC 61386

