

Contractor Packs

Hygiene Packs



Each pack contains:

- 3m conduit
- 2 fittings
- 2 locknuts

20mm I-PACK



I-PACKBUG20

3m x LPCBUG20 Conduit
2x LPC-C-FG Fittings
2x SS-M20 Locknuts



Blue Version

I-PACKWFG20

3m x LPCWFG20 Conduit
2x LPC-C-FG Fittings
2x SS-M20 Locknuts



White Version

- Hygienic design
- Smooth finish
- High IP rating
- Corrosion resistant
- High chemical & thermal resistance
- Fewer components
- Self extinguishing
- Vibration & shock tested

25mm I-PACK



I-PACKBUG25

3m x LPCBUG25 Conduit
2x LPC-C-FG Fittings
2x SS-M25 Locknuts



Blue Version

I-PACKWFG25

3m x LPCWFG25 Conduit
2x LPC-C-FG Fittings
2x SS-M25 Locknuts



White Version

- Hygienic design
- Smooth finish
- High IP rating
- Corrosion resistant
- High chemical & thermal resistance
- Fewer components
- Self extinguishing
- Vibration & shock tested

Contractor Packs

Benefits

- Simplistic ordering
- Easy storage
- Ready to use



FPAS-CP21B

Each pack contains:

- 10m conduit
- 10 fittings
- 10 locknuts



PVC white



FPL-CP20W
FPL-CP25W

M20 thread
M25 thread



- 10 metres of white corrugated upvc FPL20 or FPL25
- Pliable conduit for static applications
- Self extinguishing
- 10 white nylon Flexlok fittings and locknuts FLK20-M20W or FLK25-M25W
- IP66
- 1 part, fast fit

SLIT POLYPROPYLENE grey

FPPS-TP21G



- 10 metres of slit grey polypropylene FPP21G
- Self extinguishing
- Can be slipped over existing cables to tidy up and protect them
- 1 slit conduit insertion tool ST20

STEEL

- pvc coating - Black

IP54

FSU-CP20B M20 thread



- 10 metres of galvanised steel with PVC coating
- Temperature range -15°C to +70°C
- Self extinguishing
- High mechanical strength
- Highly flexible
- 5 M20 fixed fittings
- 5 M20 swivel fittings
- 10 steel locknuts
- IP54

NYLON

- Black

IP66



FPAS-CP21B M20 thread
FPAS-CP25B M25 thread



- 10 metres of standard weight nylon PA6 FPAS21 or FPAS25
- Low fire hazard
- Halogen free
- Self extinguishing
- Low smoke and Low toxicity
- High flexibility and fatigue life
- High impact strength
- Oil and solvent resistant
- UV resistant
- Temperature range -40°C to +120°C
- 10 FPA fittings and locknuts FPA21-M20B or FPA25-M25B
- One part, fast fit
- Removable using a screwdriver
- High pull-off strength
- Anti-vibration
- IP66
- UV resistant

PVC SPIRAL

- Black

IP65

FPC-CP20B M20 thread
FPC-CP25B M25 thread



- 10 metres of spiral reinforced pvc FPC20 or FPC25
- Highly flexible
- Accepts torsional movement
- Self extinguishing
- UV resistant
- Temperature range -5°C to +70°C
- 10 MPC fittings and locknuts
- IP65
- UV resistant
- Smooth bore

NYLON

- Black

IP66

FPYE-CP20B M20 thread
FPYE-CP25B M25 thread



- 10 metres of light weight nylon PA6 FPAL20 or FPAL25
- Flexible
- Halogen free
- Self extinguishing
- Temperature range -40°C to +120°C
- 10 Flexilok fittings and locknuts FLK20-M20B or FLK25-M25B
- IP66
- One part, fast fit

POLYPROPYLENE

- Black or Grey

IP66

FPP-CP20B M20 thread
FPP-CP25B M25 thread



- 10 metres of polypropylene FPP20 or FPP25
- Temperature range -20°C to +90°C
- Self extinguishing
- To specify grey change B to a G eg: FPP-CP20G
- 10 Flexilok (PP) fittings and locknuts FLK20-M20BPP or FLK25-M25BPP
- IP66
- One part, fast fit

Standards



Don't forget

See page 76

