



Cable Size	Gland	Standard Type Plain Seals	Pots & Seals c/w earth tails	PVC Shroud	LSF Shroud
2L1.0	RM2L1.0-10	RPS2L1.0-10	RPSL2L1.0-10	RHG20-10	RXG20-10
2L1.5	RM2L1.5-10	RPS2L1.5-10	RPSL2L1.5-10	RHG20-10	RXG20-10
2L2.5	RM2L2.5-10	RPS2L2.5-10	RPSL2L2.5-10	RHG20-10	RXG20-10
3L1.0	RM3L1.0-10	RPS3L1.0-10	RPSL3L1.0-10	RHG20-10	RXG20-10
3L1.5	RM3L1.5-10	RPS3L1.5-10	RPSL3L1.5-10	RHG20-10	RXG20-10
4L1.0	RM4L1.0-10	RPS4L1.0-10	RPSL4L1.0-10	RHG20-10	RXG20-10
4L1.5	RM4L1.5-10	RPS4L1.5-10	RPSL4L1.5-10	RHG20-10	RXG20-10

Pack Quantities: 10 Shrouds available in orange, red, white and black.  
RHG25 shrouds also available in orange, white and red

## Clips & Saddles

Cable Size	Plastic coated clips	LSF Powder coated clips	Bare copper clips	Plastic coated saddles	LSF Powder coated saddles	Cable Diameter (mm)	
	RCHJ*-50	RCHL*-50	RC(size)-50	RSFJ*-50	RSFL*-50	Covered	Bare
2L1.0	30	26	20	272	272	6.4	5.1
2L1.5	32	28	22	302	302	7.0	5.7
2L2.5	34	30	26	342	342	7.9	6.6
2L4.0	40	37	30	382	382	9.2	7.7
3L1.0	32	28	22	302	302	7.1	5.8
3L1.5	34	32	24	342	342	7.7	6.4
3L2.5	37	34	28	342	342	8.8	7.3
4L1.0	34	32	24	342	342	7.6	6.3
4L1.5	37	34	28	342	342	8.3	7.0
4L2.5	43	40	32	422	422	9.6	8.1

Pack Quantities: 50 \*Suffix Black, Red, Orange, White

**Product Description:** A range of clips and saddles to compliment fire resistant type cables in securing them to any range of surfaces.

**Raw Material:** Stamped from chamfered edge copper strip C106.

### Coating (RCHL and RSFL):

Chemical type: Polyester, Application: Electrostatic spray, Dry film thickness: From 40-100 microns (typically 50 microns).

### Mechanical Properties:

Adhesion (BS 3900 E3): Pass 1mm cross-hatch, class 0

Impact Resistance (BS 3900 E3): Pass 220"/ib indentation to 2.5mm

Flexibility (BS 3900 E11): Pass 1/4" conical mandrel

Erichsen Cupping (BS 3900 E4): Pass 8mm

Scratch Resistance (BS 3900 E2): Pass 400gms no penetration to substrate