

Pre-insulated Terminals

Blade Terminals

Material: Copper

Insulation: Polyvinyl Chloride

Max. elec. rating: ■ 19 amp

■ 27 amp

■ 48 amp


RoHS compliant



600 volts 75°C



Wire Range mm ² (AWG)	Part No.	Dimensions mm						
		D1	D3	L	L1	D2	H1	H2
	10RB	1.8	4.3	20.0	10.0	2.3	15.5	5.5
	18RB	1.8	4.3	28.0	10.0	2.5	23.5	5.5
	9BB	2.3	4.8	20.0	10.0	2.3	15.5	5.5
	18BB	2.3	4.8	28.0	10.0	2.5	23.5	5.5
	10YB	3.5	6.5	23.5	13.5	3.0	16.7	6.5
	16YB	3.5	6.5	29.5	13.5	4.8	22.5	6.5
	18YB	3.5	6.5	31.5	13.5	2.1	24.5	6.5



Pack Quantity: 100

Pin Terminals

Material: Copper

Insulation: Polyvinyl Chloride

Max. elec. rating: ■ 19 amp


■ 27 amp

■ 48 amp

600 volts 75°C



RoHS compliant



Wire Range mm ² (AWG)	Part No.	Dimensions mm						
		D1	D4	L	L1	D2	H1	H2
	95RP	1.8	4.3	19.0	10.0	1.9	14.6	5.5
	12RP	1.8	4.3	22.0	10.0	1.9	17.6	5.5
	95BP	2.3	4.7	19.0	10.0	1.9	14.6	5.5
	12BP	2.3	4.7	22.0	10.0	1.9	17.6	5.5
	14YP	3.5	6.6	28.0	13.5	2.7	21.0	6.5

Pack Quantity: 100

Vibration resistant versions available on request.

Un-insulated & Un-insulated High Temperature Terminals available on request.