

Cable Jointing

CELLPACK

Cellpack Straight Cable Joints



Selection chart for armoured cables.

Straight through joint selection chart

Cellpack - Clear Straight - Through Joint Type SJK.

Conductors: Copper to copper - compression splices or mechanical connectors suitable.

Copper to aluminium/aluminium to aluminium - mechanical connectors only.

Part No.	Cable Size (mm ²)	No. of cores	Min - Max cable dia. (mm)	Connectors Required (one connector required per core)	
				Compression	Mechanical
SJK1516	1.5	2	7-30	Included	-
SJK1516	1.5	3	7-30	Included	-
SJK1516	1.5	4	7-30	Included	-
SJK1516	2.5	2	7-30	Included	-
SJK1516	2.5	3	7-30	Included	-
SJK1516	2.5	4	7-30	Included	-
SJK1516	4	2	7-30	Included	-
SJK1516	4	3	7-30	Included	-
SJK1516	4	4	7-30	Included	-
SJK1516	6	2	7-30	Included	-
SJK1516	6	3	7-30	Included	-
SJK1516	6	4	7-30	Included	-
SJK1516	10	2	7-30	Included	-
SJK1516	10	3	7-30	Included	-
SJK1516	10	4	7-30	Included	-
SJK1516	16	2	7-30	Included	-
SJK1516	16	3	7-30	Included	-
SJK1516	16	4	7-30	Included	-

All joints are supplied with clear mould, resin pack, earth continuity, gloves, sealing tape.

Cable connectors included up to 16mm².

Earth braid can be supplied separately.

Cable Jointing

CELLPACK

Cellpack Straight Cable Joints



Selection chart for armoured cables.

Straight through joint selection chart

Cellpack - Clear Straight - Through Joint Type SJK.

Conductors: Copper to copper - compression splices or mechanical connectors suitable.

Copper to aluminium/aluminium to aluminium - mechanical connectors only.

Part No.	Cable Size (mm ²)	No. of cores	Min - Max cable dia. (mm)	Connectors Required (one connector required per core)	
				Compression	Mechanical
SJK1	1.5	2	7-30	-	Included
SJK1	1.5	3	7-30	-	Included
SJK1	1.5	4	7-30	-	Included
SJK1	2.5	2	7-30	-	Included
SJK1	2.5	3	7-30	-	Included
SJK1	2.5	4	7-30	-	Included
SJK1	4	2	7-30	-	Included
SJK1	4	3	7-30	-	Included
SJK1	4	4	7-30	Included	-
SJK1	6	2	7-30	Included	-
SJK1	6	3	7-30	Included	-
SJK1	6	4	7-30	Included	-
SJK2	10	2	14-30	Included	-
SJK2	10	3	14-30	Included	-
SJK2	10	4	14-30	Included	-

SJK1: 15 amp strip connectors

SJK2: 6, 10, 16mm² splices

All joints are supplied with clear mould, resin pack, earth continuity, gloves, sealing tape.

Cable connectors included up to 35mm².

Earth braid can be supplied separately.

CELLPACK

Cellpack Straight Cable Joints



Selection chart for armoured cables.

Straight through joint selection chart

Cellpack - Clear Straight - Through Joint Type SJK.

Conductors: Copper to copper - compression splices or mechanical connectors suitable.
Copper to aluminium/aluminium to aluminium - mechanical connectors only.

Part No.	Cable Size (mm ²)	No. of cores	Min - Max cable dia. (mm)	Connectors Required (one connector required per core)	
				Compression	Mechanical
SJK2	16	2	14-30	Included	-
SJK2	16	3	14-30	Included	-
SJK2	16	4	14-30	Included	-
SJK2	25	2	14-30	Included	-
SJK3	25	3	20-37	Included	-
SJK4	25	4	25-42	-	(P1) Included
SJK3	35	2	20-37	Included	-
SJK4	35	3	25-42	-	(P1) Included
SJK4	35	4	25-42	-	(P1) Included
SJK3	50	2	20-37	Included	-
SJK4	50	3	25-42	50BS	-
SJK4	50	4	25-42	50BS	-

Copper to Aluminium/Aluminium to Aluminium

Part No.	Cable Size (mm ²)	No. of cores	Min - Max cable dia. (mm)	Connectors Required (one connector required per core)	
				Compression	Mechanical
SJK5S	50	2	25-42	n/a	UM1
SJK5	50	3	33-55	n/a	UM1
SJK5	50	4	33-55	n/a	UM1

SJK2: 6, 10, 16mm² splices

SJK3: 16, 25, 35mm² splices

SJK4: P1 mechanical connectors

All joints are supplied with clear mould, resin pack, earth continuity, gloves, sealing tape.

Cable connectors included up to 35mm².

Earth braid can be supplied separately.

CELLPACK

Cellpack Straight Cable Joints



Straight through joint selection chart

Cellpack - Clear Straight - Through Joint Type SJK.

Selection chart for armoured cables.

Conductors: Copper to copper - compression splices or mechanical connectors suitable.

Copper to aluminium/aluminium to aluminium - mechanical connectors only.

Part No.	Cable Size (mm ²)	No. of cores	Min - Max cable dia. (mm)	Connectors Required (one connector required per core)	
				Compression	Mechanical
SJK4	70	2	25-42	70BS	-
SJK5S	70	2	33-55	-	UM1
SJK5	70	3	33-55	70BS	UM1
SJK5	70	4	33-55	70BS	UM1
SJK4	95	2	25-42	95BS	UM1
SJK5	95	3	33-55	95BS	UM1
SJK5	95	4	33-55	95BS	-
SJK6S	95	4	45-74	-	UM1

Copper to Aluminium/Aluminium to Aluminium

Part No.	Cable Size (mm ²)	No. of cores	Min - Max cable dia. (mm)	Connectors Required (one connector required per core)	
				Compression	Mechanical
SJK6S	95	4	45-74	n/a	UM1

All joints are supplied with clear mould, resin pack, earth continuity, gloves, sealing tape.

Cable connectors included up to 35mm².

Earth braid can be supplied separately.

CELLPACK

Cellpack Straight Cable Joints



Straight through joint selection chart

Cellpack - Clear Straight - Through Joint Type SJK.

Selection chart for armoured cables.

Conductors: Copper to copper - compression splices or mechanical connectors suitable.

Copper to aluminium/aluminium to aluminium - mechanical connectors only.

Part No.	Cable Size (mm ²)	No. of cores	Min - Max cable dia. (mm)	Connectors Required (one connector required per core)	
				Compression	Mechanical
SJK5	120	2	33-55	120BS	UM2
SJK5	120	3	33-55	120BS	UM2
SJK6	120	4	45-74	120BS	UM2
SJK5	150	2	33-55	150BS	UM2
SJK6	150	3	45-74	150BS	UM2
SJK6	150	4	45-74	150BS	UM2
SJK5	185	2	33-55	185BS	-
SJK6S	185	2	45-74	-	UM3
SJK6	185	3	45-74	185BS	UM3
SJK6	185	4	45-74	185BS	-
SJK7S	185	4	50-95	-	UM3
SJK6	240	2	45-74	240BS	UM3
SJK6	240	3	45-74	240BS	UM3
SJK7	240	4	50-95	240BS	UM3
SJK6	300	2	45-74	300BS	UM3
SJK7	300	3	50-95	300BS	UM3
SJK7	300	4	50-95	300BS	UM3
SJK7	400	2	50-95	400BS	MF1/4
SJK7	400	3	50-95	400BS	MF1/4
SJK7	400	4	50-95	400BS	MF1/4

All joints are supplied with clear mould, resin pack, earth continuity, gloves, sealing tape.

Cable connectors included up to 35mm².

Earth braid can be supplied separately.

Cable Jointing

CELLPACK



For copper and aluminium cables.

Multi-Core Cables Copper Conductors

For use with PVC Insulated - PVC Sheathed Armoured cables

Joint ref.	Nominal area of conductor (mm ²)	No. of cores
SJK1	1.5	5
SJK2	1.5	7
SJK2	1.5	10
SJK3	1.5	12
SJK4	1.5	19
SJK4	1.5	22
SJK4	1.5	27
SJK4	1.5	30
SJK4	1.5	40
SJK5	1.5	48

Joint ref.	Nominal area of conductor (mm ²)	No. of cores
SJK1	2.5	5
SJK2	2.5	7
SJK2	2.5	10
SJK3	2.5	12
SJK4	2.5	19
SJK4	2.5	22
SJK4	2.5	27
SJK4	2.5	30
SJK4	2.5	40
SJK5	2.5	48

Multi-Pair Cables Copper Conductors

For use with PVC Insulated - PVC Sheathed Armoured cables

Joint ref.	Nominal area of conductor (mm ²)	No. of pairs
SJK1	0.5	2
SJK2	0.5	5
SJK4	0.5	10
SJK4	0.5	15
SJK4	0.5	20
SJK5	0.5	25
SJK5	0.5	30
SJK5	0.5	40
SJK5	0.5	50
SJK6	0.5	100

Joint ref.	Nominal area of conductor (mm ²)	No. of pairs
SJK1	0.9	2
SJK2	0.9	5
SJK4	0.9	10
SJK4	0.9	15
SJK4	0.9	20
SJK5	0.9	25
SJK5	0.9	30
SJK5	0.9	40
SJK5	0.9	50
SJK6	0.9	100

Joint ref.	Nominal area of conductor (mm ²)	No. of pairs
SJK1	1.5	2
SJK2	1.5	5
SJK4	1.5	10
SJK4	1.5	15
SJK4	1.5	20
SJK5	1.5	25
SJK5	1.5	30
SJK5	1.5	40
SJK5	1.5	50
SJK6	1.5	100

Cable connectors for both Multi-core and Multi-pair cables supplied only on request. All joints supplied with clear mould, resin pack, earth continuity, gloves and sealing tape.