

# Anchor Bolts

## Concrete Screws

- Grade 8.8 self tapping anchor
- Gives high performance in a variety of solid and hollow materials
- Threading action provides a positive and safe anchorage
- Simple to install
- Can be removed and re-fixed

- Low expansion forces means close to edge fixing is possible
- Bright zinc plated and yellow passivated
- Produced and engineered from high quality carbon steel

### Applications

Highly suitable for a wide range of construction materials including concrete, stone, brick & block.



### Range Information

Product Code	Size mm	Drill Diameter mm	Anchor Length mm	Maximum Fixture Thickness mm	Minimum Hole Depth mm	Driver Type	Unit Qty
--------------	---------	-------------------	------------------	------------------------------	-----------------------	-------------	----------

#### Hexagon Flange Head

086-418-025	6x50	6	50	20	40	10mm A/F	100
086-418-030	6x75	6	75	45	40	10mm A/F	100
086-418-035	6x100	6	100	55	40	10mm A/F	100
086-418-045	6x130	6	130	85	40	10mm A/F	100
086-418-050	6x150	6	150	105	40	10mm A/F	100

#### Hexagon Head

086-418-055	8x60	8	60	20	55	15mm A/F	100
086-418-060	8x75	8	75	35	55	15mm A/F	100
086-418-065	8x100	8	100	60	55	15mm A/F	100
086-418-067	8x130	8	130	90	55	15mm A/F	50
086-418-068	8x150	8	150	110	55	15mm A/F	50
086-418-070	10x60	10	60	10	70	17mm A/F	50
086-418-075	10x75	10	75	25	70	17mm A/F	50
086-418-080	10x100	10	100	50	70	17mm A/F	50
086-418-083	10x130	10	130	80	70	17mm A/F	25
086-418-085	10x150	10	150	100	70	17mm A/F	25
086-418-090	12x75	12	75	15	85	19mm A/F	50
086-418-095	12x100	12	100	40	85	19mm A/F	50
086-418-100	12x130	12	130	70	85	19mm A/F	25
086-418-105	12x150	12	150	90	85	19mm A/F	20
086-418-110	12x200	12	200	140	85	19mm A/F	20

#### Countersunk Head

086-418-210	6x75	6	75	45	40	Torx T-30	50
086-418-215	6x100	6	100	55	50	Torx T-30	50

## Hexagon Rod Hangers

- High performance fixing for many solid materials
- Threading action provides a positive and safe anchorage
- Simple & fast to install
- Can be removed and re-fixed

- Engineered from high quality carbon steel
- Bright zinc plated finish

### Applications

Ideal for suspending steel threaded rods to support pipes, fire protection equipment, electrical conduit, cable tray and lowered ceiling systems.



### Range Information

Product Code	Internal Thread Size mm	Drill Diameter mm	Overall Length mm	Anchor Thread Length mm	Min. Hole Depth mm	Hexagon Size AF mm	Unit Qty
086-418-300	M8	6	55	40	50	13	50
086-418-310	M10	6	55	40	50	13	50
086-418-320	M8/10	6	75	40	50	17	50