

CIRCULAR DRY LINING AND ADAPTABLE BOXES

Circular flush mounted boxes.

Product information

- Wide securing flange to prevent box passing through cavity
- For board thickness from 9 to 32mm measured from the face of the board
- Swivelling snap out clamps fix the box firmly into position (screws provided)

Standard Colour
WH
WH: White

Colour options: Other colours are available but may be subject to minimum order quantities and longer lead times. For further information please contact the Technical Team on +44 (0)1424 856688.



Wide securing flanges

FIRE SECURITY

Intumescent fire barrier pads

Fire Barrier Pads are now a requirement of Document B of the UK Building Regulations. For information on Fire Barrier Pads please refer to page 140 in our Fire and Security section or contact our Technical Team on +44 (0)1424 856688.



Dry lining boxes



Double back entry - loop in 34mm internal depth (white clamps)

code	fix. centre	pack
MDCRB2WH	50.8/60.3mm	10

Ø cut out = 70mm

Moulded enclosures



Moulded enclosure unit (Adaptable box)

code	external size	pack
MTAB75AWH	81 x 81 x 67mm	10
MTAB100AWH	106 x 106 x 67mm	10
MTAB150BWH	155 x 155 x 92mm	4

Also available in black

Product information

- Degree of protection IP66.
- Raised pads in base of box to allow accessory mounting nuts to be recessed.
- Silicon rubber lid seal supplied as standard.
- Brass inserts M3.5 with stainless countersunk fixing screws.
- Suitable for drilling or cutting.
- Raised flat lid for strength.

Earth rod box



Earth rod box Green only

code	external size	pack
MECB75GN	81 x 81 x 67mm	10

Product information

- Protects connection to earth rod.
- Earth rod/cable entry \varnothing 7-10.5mm.

p260

Technical
Information