

# Fixing Band

## Plastic Coated



- All purpose flexible fixing band
- Pre punched holes to enable fixing with bolts, screws, nails etc.
- Easy to cut and bend to shape
- Manufactured from steel & then plastic coated
- Flexible yet strong
- Supplied in 10 metre rolls

### Applications

Used for securing, supporting and strapping of cables, guttering, fencing, lighting, pipework, trunking and ducting and is ideal for all suspension applications.

### Range Information

Product Code	Colour	Thickness mm	Fixing Hole Diameter mm	Unit Qty	Carton Qty
<b>12mm Band Width</b>					
061-130-005	White	1	5	1	20
061-130-010	Black	1	5	1	20
061-130-025	Red	1	5	1	20
<b>17mm Band Width</b>					
061-130-030	White	1	7	1	10
061-130-035	Black	1	7	1	10

# Drop In Anchors

## Wedge Anchors

### Hammerset Anchors

- An internally threaded socket anchor for use with bolts or threaded rod of any length
- May be set flush or at depth
- Secure and controlled expansion with the setting tool
- Built in expansion cone
- Medium duty fixing
- Zinc plated & yellow passivated

### Applications

Ideal for suspension/bolting, ductwork, cable tray and holding down applications. Particularly suitable for use in concrete, stone and solid brick.



### Range Information

Product Code	Thread Diameter	Anchor Hole Diameter mm	Anchor Length mm	Max. Internal Thread Length mm	Min. Hole Depth mm	Unit Qty
<b>Standard Type</b>						
127-320-005	M6	8	25	11	27	100
127-320-010	M8	10	30	13	32	100
127-320-015	M10	12	40	19	42	50
127-320-020	M12	16	50	23	53	25
127-320-025	M16	20	65	28	68	25
<b>Flanged Type</b>						
127-320-110	M6	8	25	11	27	100
127-320-120	M8	10	30	13	32	100
127-320-130	M10	12	40	17	42	50

## Drop In Anchor Setting Tools

- Setting punch for drop in anchors
- The tool drives the steel expander plug into the anchor to a controlled depth

### Range Information

Product Code	Suitable for Thread Size	Unit Qty
127-321-005	M6	1
127-321-010	M8	1
127-321-015	M10	1
127-321-020	M12	1
127-321-025	M16	1

