

Meteor Maxi™ LED

PRODUCT OVERVIEW

The Meteor Maxi benefits from higher lumen output and a larger housing, making it a true 8W replacement.

Now with optional remote control! *

Measuring 110mm (W) 352mm (L) 57mm (D) the Meteor Maxi LED fitting has a lumen output of 124 in emergency mode from a 10 LED array, a hinged gear tray allows for easy installation.

The unit boasts an aesthetically pleasing design and is virtually maintenance free. The biggest success, as with the majority of our LED products, is that it operates on 20% of the power that a standard 8W fluorescent would consume.




PRODUCT FEATURES

- Dimensions: 110mm (W) 352mm (L) 57mm (D)
- Light source: LED
- Power consumption: 5W
- Uses typically 80% less power than that of an 8W fluorescent
- Maintained or non-maintained 3 hour emergency backup
- Compliance: BS EN 60598-2-22 and other relevant standards
- Other accessories: Semi-recessing kit and diffuser with legend
- Now with optional remote control
- Complete with exit legend kit
- Incorporates remote control testing facility
- Allows testing without disruption
- Unit automatically tests
- Universal remote control with approx range of 10m

PHOTOMETRIC SPACING DATA (1 lux)

Mounting height	↔		↔		↔		↔	
	0.5 lux	1 lux	0.5 lux	1 lux	0.5 lux	1 lux	0.5 lux	1 lux
2.5m	3.25	3.30	6.50	6.60	4.90	4.35	2.45	2.20
4m	3.60	4.00	7.20	8.00	6.00	4.55	3.00	2.30
6m	3.70	N/A	7.40	N/A	6.15	N/A	3.10	N/A



Remote Control Feature

Press once for 5 second monthly test

Press twice for three hour yearly test

LED indicators confirm pass/ fail status

* Remote Control Option available Q4 2017

PRODUCT CODE	DESCRIPTION
E/MM/M3/LED	Meteor Maxi LED 3 Hour Maintained Emergency Light C/W Remote Control
E/EM/RC	Optional Remote Control
E/BEZ/MM	Meteor Maxi Semi Recessing Bezel
B/BATT/MM	Meteor Maxi LED Battery 3.6V 1500mAH with connector
E/PIC/ME/LED/PACK	Meteor Maxi Pictogram Pack - (AD, AL, AR & AU)