

Brook 2

PRODUCT FEATURES

- Now with increased light output
- Dimensions: 115mm (W) 350mm (L) 75mm (D)
- Cut out dimensions for bezel: 83mm - 337mm
- Light source: LED (50 in unit)
- Power consumption: 7.3W
- Uses typically 80% less power than that of an 8W fluorescent
- Lumen output: 320 lm (210lm emergency mode)
- Material: Polycarbonate diffuser and body
- IP Rating: IP65
- Maintained or non-maintained 3 hour emergency backup
- Weight: 0.95Kg
- Compliance: BS EN 60598-2-22 and other relevant standards
- Other accessories: Semi-recessing bezel available



LED 7.3W 210 lm IP65 0.95Kg

CE F OPTIONS Self Test IP65 LED

PHOTOMETRIC SPACING DATA (1 lux)

Mounting height	↔	↔	↔	↔
2.5m	2.6	7.7	8.9	2.9
4m	2.6	4.9	8.9	2.7

PRODUCT CODE	DESCRIPTION
E/BK/M3/LED/2	Brook self contained, 3 hour maintained emergency LED light
E/BK/M3/LED/2/ST	Brook self contained, self-test 3 hour maintained emergency LED light
E/BZ/KIT/BROOK/WH	Brook semi-recessing bezel
E/PIC/ME/LED/PACK	Brook pictogram pack - AD/AL/AR/AU

REPLACEMENT PARTS

B/BATT/BROOK/2	Brook battery - 3 cell NiCd
----------------	-----------------------------

NEW Stratos

PRODUCT FEATURES

- Dimensions: 260mm (L) 140mm (W) 40mm (D)
- Standard 1W (193lm) or High Output 2W (235lm)
- IP Rating: IP65
- Weight: 0.4KG
- Semi Recessing Kit Option
- Drop Down Exit Blade Option
- Compliance: BS EN 60598-2-22 and other relevant standards
- Central Battery 24V, 50V, 110V & 230V AC/DC/Slave fittings
- Supplied with complete legend pack
- Viewing Distance: 25m



Legend



Drop Down Blade Option



CE F IP65 LED 1W 2W 193 lm 235lm IP65 0.4Kg

PRODUCT CODE	DESCRIPTION
E/STRATOS/24	Stratos 7x LED- 1 W, IP65, 24 volt AC/DC slave bulkhead c/w exit sign pictogram
E/STRATOS/50	Stratos 7x LED- 1 W, IP65, 50 volt AC/DC slave bulkhead c/w exit sign pictogram
E/STRATOS/110	Stratos 7x LED- 1 W, IP65, 110 volt AC/DC slave bulkhead c/w exit sign pictogram
E/STRATOS/230	Stratos 7x LED- 1 W, IP65, 230 volt AC/DC slave bulkhead c/w exit sign pictogram
E/STRATOS/M3	Stratos 7x LED- 1 W, IP65, 3 hr maintained bulkhead c/w exit sign pictogram
E/STRATOS/M3/2W	Stratos 7x LED- 2 W, IP65, 3 hr maintained bulkhead c/w exit sign pictogram
E/STRATOS/REC/KIT	Stratos Semi Recessing Kit
E/STRATOS/PIC/KIT	Stratos Hanging Blade legend c/w exit sign pictogram