

Meteor™ LED

PRODUCT OVERVIEW

This popular fitting is now available with a self-test option.

Weighing in at only 360g and measuring 260x100x61mm the Meteor LED fitting has a lumen output of 52 in emergency mode from a 10 LED array, a hinged gear tray allows for easy installation.

The unit boasts an aesthetically pleasing design and is virtually maintenance free. The biggest success, as with the majority of our LED products, is that it operates on 20% of the power that a standard 8W fluorescent would consume.

Convert your Meteor Bulkhead fitting into an attractive emergency exit sign with a blade and diffuser kit.



E/ME/M3/LED/IP65



PRODUCT FEATURES

- Dimensions: 100mm (W) 260mm (L) 61mm (D)
- Cut out dimensions: 230mm (L) 85mm (W)
- Light source: LED
- Power consumption: 3W
- Uses typically 80% less power than that of an 8W fluorescent
- Maintained or non-maintained 3 hour emergency backup
- Weight: 0.36Kg
- Compliance: BS EN 60598-2-22 and other relevant standards
- Other accessories: Semi-recessing kit and diffuser with legend



PHOTOMETRIC SPACING DATA (1 lux)

Mounting height	↔	↔	↔	↔
2.5m	2.4	5.8	5.4	2.4
4m	1.0	4.9	5.2	1.0



E/PIC/ME/LED/BLADE - Bulkhead shown with NEW Blade & Diffuser Kit

PRODUCT CODE	DESCRIPTION
E/ME/M3/LED/IP65	Meteor low profile LED bulkhead complete with 10 LED array, IP65 version
E/ME/M3/LED/IP65/ST	Meteor IP65 low profile LED Bulkhead complete with 10 LED array, self test version
ACCESSORIES	
E/ME/LED/SRK/1	Meteor LED semi-recessing kit
E/PIC/ME/LED/PACK	Meteor LED sticker pictogram pack - (AD, AL, AR & AU) - Viewing distance 20m
E/PIC/ME/LED/BLADE	Meteor LED Blade and Diffuser kit (Achieving IP65 rating) Light fitting not included - Viewing distance 20m
REPLACEMENT PARTS	
B/BATT/METEOR/LED	Meteor LED battery - 3 cell stick AA NiCd 0.Ah