

Metallic conduit systems

Type A & B - Adaptasteel

Type A - Adaptasteel

Straight fitting - Fixed external male thread / Materials: Nickel plated brass



Part no.	Nominal conduit size (mm)	US conduit size (in)	Metric thread
SPL16/M16/A	16	3/8"	M16
SPL16/M20/A	16	3/8"	M20
SPL20/M20/A	20	1/2"	M20
SPL25/M25/A	25	3/4"	M25
SPL32/M32/A	32	1"	M32

For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Approvals



IP rating

Appropriate conduit

For use with: Type SPL / SPLHC / SPUL / SPL-EF / LFH-SPL

IP40	N/A
IP65	N/A
IP66	N/A
IP67	Yes
IP68	N/A
IP69	N/A

Temperature range

Static applications: -65°C to +105°C

Moving applications: -45°C to +150°C

Type B - Adaptasteel

Straight fitting - Fixed external male thread / Materials: Nickel plated brass



Part no.	Nominal conduit size (mm)	US conduit size (in)	Metric thread
SPL16/M16/B	16	3/8"	M16
SPL16/M20/B	16	3/8"	M20
SPL20/M20/B	20	1/2"	M20
SPL25/M25/B	25	3/4"	M25
SPL32/M32/B	32	1"	M32

For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Approvals



IP rating

Appropriate conduit

For use with: Type SPL / SPLHC / SPUL / SPL-EF / LFH-SPL

IP40	N/A
IP65	N/A
IP66	N/A
IP67	Yes
IP68	N/A
IP69	N/A

Temperature range

Static applications: -65°C to +105°C

Moving applications: -45°C to +150°C

Fitting characteristics

