


## Metallic conduit systems



### Type S & SS - Adaptasteel

**Type S - Adaptasteel**

Inherent low fire hazard steel conduit / Materials: Galvanised steel - general purpose


	Part no.	Nominal conduit size (mm)	Outside diameter (mm)	Inside diameter (mm)	Min. bend radius (mm)	Reel length (m)
	S10	10	9.1	7.0	25	25, 50
	S12	12	13.0	10.3	30	10, 25, 50
	S16	16	16.0	13.0	35	10, 25, 50
	S20	20	20.5	16.9	45	10, 25, 50
	S25	25	25.0	21.4	55	10, 25, 50
	S32	32	32.0	28.1	60	10, 25
	S40	40	42.5	37.7	80	10, 25
	S50	50	53.0	48.4	90	10, 25
	S63	63	62.5	57.5	115	10
	S75	75	77.0	70.0	150	10

To order quote part no, & reel length, e.g. S12/25M



Approvals	IP rating	Appropriate fitting	Temperature range	UV resistance
	For use with: Type S		Static applications: -50°C to +300°C	Very high
	IP40	Type S - Type A, B, F & C	Moving applications: -45°C to +250°C	
	IP65	N/A	<b>Flexibility &amp; fatigue life</b>	
	IP66	N/A	High flexibility - High fatigue life	
	IP67	N/A	<b>Fire Performance &amp; EMI Screen</b>	
	IP68	N/A		
	IP69	N/A		

**Type S - Adaptasteel**

Inherent low fire hazard steel conduit / Materials: Galvanised steel - general purpose

	Part no.	Nominal conduit size (mm)	Outside diameter (mm)	Inside diameter (mm)	Min. bend radius (mm)	Reel length (m)
	SS10	10	9.0	6.8	25	25, 50
	SS12	12	13.0	10.3	30	25, 50
	SS16	16	16.0	13	35	10, 25, 50
	SS20	20	20.5	16.9	45	10, 25, 50
	SS25	25	25.0	21.4	55	10, 25, 50
	SS32	32	32.0	28.1	60	10, 25

To order quote part no, & reel length, e.g. S12/25M

Approvals	IP rating	Appropriate fitting	Temperature range	UV resistance
	For use with: Type S		Static applications: -50°C to +350°C	Very high
	IP40	Type S - Type A, B, F & C	Moving applications: -45°C to +250°C	
	IP65	N/A	<b>Flexibility &amp; fatigue life</b>	
	IP66	N/A	High flexibility - High fatigue life	
	IP67	N/A	<b>Fire Performance &amp; EMI Screen</b>	
	IP68	N/A		
	IP69	N/A		