

Metallic conduit systems

Type A & B - Adaptasteel

Type A - Adaptasteel

Straight fitting - Fixed external male thread / Materials: Nickel plated brass

	Nominal conduit size			Nominal conduit size		
	Part no.	(mm)	Metric thread	Part no.	(mm)	PG thread
	S10/M12/A	10	M12	S10/PG7/A	10	PG7
	S12/M16/A	12	M16	S12/PG9/A	12	PG9
	S16/M16/A	16	M16	S16/PG11/A	16	PG11
	S16/M20/A	16	M20	-	-	-
	S20/M20/A	20	M20	S20/PG16/A	20	PG16
	S25/M25/A	25	M25	S25/PG21/A	25	PG21
	S32/M32/A	32	M32	S32/PG29/A	32	PG29
	S40/M40/A	40	M40	S40/PG36/A	40	PG36
	S50/M50/A	50	M50	S50/PG42/A	50	PG42
	S63/M63/A	63	M63	S63/PG48/A	63	PG48
	S75/M75/A	75	M75			

For insertion into knockouts using a locknut (order locknut separately)

Approvals



IP rating

Appropriate conduit

For use with: Type S / SS

IP40	Yes
IP65	N/A
IP66	N/A
IP67	N/A
IP68	N/A
IP69	N/A

Temperature range

Static applications: -50°C to +300°C

Moving applications: -45°C to +250°C

Type B - Adaptasteel

Straight fitting - Swivel external male thread / Materials: Nickel plated brass

	Nominal conduit size			Nominal conduit size		
	Part no.	(mm)	Metric thread	Part no.	(mm)	PG thread
	S10/M12/B	10	M12	S10/PG7/B	10	PG7
	S12/M16/B	12	M16	S12/PG9/B	12	PG9
	S16/M16/B	16	M16	S16/PG11/B	16	PG11
	S16/M20/B	16	M20	-	-	-
	S20/M20/B	20	M20	S20/PG16/B	20	PG16
	S25/M25/B	25	M25	S25/PG21/B	25	PG21
	S32/M32/B	32	M32	S32/PG29/B	32	PG29
	S40/M40/B	40	M40	S40/PG36/B	40	PG36
	S50/M50/B	50	M50	S50/PG42/B	50	PG42

For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Approvals



IP rating

Appropriate conduit

For use with: Type S / SS

IP40	Yes
IP65	N/A
IP66	N/A
IP67	N/A
IP68	N/A
IP69	N/A

Temperature range

Static applications: -50°C to +300°C

Moving applications: -45°C to +250°C

Fitting characteristics

